



---

**DECLARATION OF PERFORMANCE**

**Prelasti S/ST**

**N° DOP Prelasti S/ST-2020.02.24**

---

**1. Unique identification code of the product type:**

Prelasti S/ST.

**2. Identification of the construction product:**

See product label and/or packaging.

**3. Intended use or uses:**

Prelasti S/ST (Standard) is an unreinforced EPDM waterproofing membrane produced in two ply. The product comes in black colour and has a surface texture on both sides. The range of use is waterproofing of roofs.

**4. Contact address of manufacturer/trading company:**

SealEco AB  
P.O.Box 514  
SE-331 25 Värnamo  
Sweden

**5. System or systems of assessment and constancy of performance:**

System 2+.

**6. Notified body / Certification n°:**

Notified body: 0958 SGS INTRON Certificatie BV  
FPC: 0958-CPR-2036/1

## 7. Declared performance

Characteristic	Test method	Unit	Performance		Harmonised Standard
			Value	Expr. of result	
Water tightness	EN 1928 (B)	10 kPa	Pass	Pass/Fail	EN 13956:2012
Tensile strength	EN 12311-2 (A)	N/mm <sup>2</sup>	9	≥ MLV	
Elongation at break	EN 12311-2 (B)	%	300	≥ MLV	
Root resistance	EN 13948/FLL		Pass	Pass/Fail	
Resistance to static load	EN 12730 (A/B)	kg	1.0 mm: NPD ≥ 1.2 mm: 20	≥ MLV	
Resistance to impact	EN 12691 (B)	mm	1.0 mm: NPD ≥ 1.2 mm: 1000	≥ MLV	
Tear resistance	EN 12310-2	N	1.0 mm: NPD ≥ 1.2 mm: 60	≥ MLV	
Peel strength of joint	EN 12316-2	N/50 mm	100	≥ MLV	
Shear strength of joint	EN 12317-2	N/50 mm	200	≥ MLV	
Durability	EN 1297	Classification	Pass	Pass/Fail	
Foldability	EN 495-5	°C	-40	> MLV	
External fire performance	EN 13501-5		F <sub>ROOF</sub> (t)	Classification	
Reaction to fire	EN 13501-1		Class E	Classification	
Dangerous substances	EU construction directive		No dangerous substances	MDV	

NPD = No Performance Determined  
 MDV= Manufacturer's Declared Value  
 MLV = Manufacturer's Limiting Value.

## 8. Declaration

The performance of the product is in conformity with the declared performance. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Värnamo, 24-02-2020



Jörgen Skärin  
 R&D SealEco AB